



AM-5000

Dental Microscope

ALLTION (GUANGXI) INSTRUMENT CO., LTD
Add: No.10,3rd road, wuzhou industrial park, wuzhou city,
guangxi province, 543000 china
Tel: 0774-2836101, 2836102
Fax: 0774-2836192
E-MAIL: sales@alltion.com
WEB SITE: www.alltion.com, www.alltion-microscope.com




Flexible Optics Rotating Assembly (FORA)
Integrated Depth of Field Strengthen Device
Fluorescence and White Illumination
Built-in 4K Camera System
198-455mm Variable objective lens
Manual 6-step magnification
Single-handed operation




Seven Features

- Flexible optics rotating assembly (FORA)
- Integrated depth of field strengthen device
- Fluorescence and white illumination
- Built-in 4K camera system
- 198-455mm Variable objective lens
- Manual 6-step magnification
- Single-handed operation




Single-Handed Operation

Without taking your hand off the handle, the magnification knob, Freeze Knob, Photo and Video Recording Knob and variable objective lens can be operated with your thumb, making it easy to perform common functions with one hand.



Flexible Optics Rotating Assembly (FORA) Pendulum Function by FORA Is Available

FORA including 90°binocular extender, pendulum rotation device and beam splitter (2.8/5.5). It allows operator to remain his natural and straight posture while he is observing the patient with a certain angle. The operator can change the direction of the optical pod only, while keeping the binocular at its position.




Built-in 4K Camera System

- Photograph
- Video recording
- Freeze
- USB storage
- Double HDMI channel output
- Playback
- Contrasting photo-photo, photo-live images
- Mouse operated
- Built-in WIFI function
- Wireless foot control

Manual 6-Step Magnification


With the 198-455mm variable objective lens, the magnification range is from 1.4X to 22.8X 1 more step than the conventional 5-step magnification for higher magnification



Fluorescence and White Illumination

2 modes of illumination, white and fluorescence. The light switch knob is linked to the anti-violet shield, which is automatically moved into the light path to protect the operators' eyes when switched to fluorescence mode. Fluorescence mode: aids in the identification of natural tooth tissue and artificial material boundaries. AM-5000 fluorescence mode helps the operators to distinguish the natural hard tooth tissue from the dental composite resin material. This clear visual distinction not only help the operator to quickly target the affected area, but also save operators' valuable chair time during the excavation process.

Light switch knob



198-455mm Variable Objective Lens

Support wide working distance: 198-455mm
Suitable for operators of different heights
Objective lens 250mm/300mm/400mm for options

Main Specification of AM-5000 Series Dental Microscope

	Type	Standard	Optional
Optic	Magnification	Manual 6-step magnification	
	Objective lens	198-455mm Variable objective lens	Objective lens(250mm/300mm/400mm)
	Magnification range	1.4X-22.8X	
	Binocular	0-180°Inclined binocular head with knob of pupillary distance adjustment	45°Binocular/straight binocular
	Range of interpupillary distance	50mm-75mm	
	Eyepiece	12.5X/18mm	10X/21mm
	Glass technology	Premium quality apochromatic technology	
Illumination	Diopter	±7D	
	Optical extender		30° Binocular extender+ beam splitter+rotation device; 45°/90°binocular extender with angle rotation device
	LED	Long-life LED>50,000 hours	
	Illumination	Illumination up to 80,000lx with a 250mm fixed focus objective	
	Color rendering	≥85%	
Power supply	Color Temperature	5500K	
	Light spot	Three types of light spot: maximum/ medium/minimum(without filter) Two types of filter:green/ yellow	
	Fluorescence mode		Fluorescence mode
Support system	Camera	Built-in 4K camera(see the table below for detailed parameters)	
	Rated Voltage	Input: AC100-240V/50/60 HZ; output: DC12V/3A	
	Input power	25-80VA	
Support system		Floor Stand	Fixed floor stand/floor stand with 950 pantograph arm/ceiling mount/low position wall mount/high position wall mount/ table mount/table clamp mount


Specification of Built-in 4K Camera

Interface	1/1.8" SONY 8 million pixel high-performance, high sensitivity and low-noise CMOS
Resolution	HDMI 2.0 1pc/ USB 2.0 1pc (for mouse)/USB 3.0 1pc (for connect USB flash disk)/ 3.5 audio interface 1pc (for sound recording)
Storage	4K (3840*2160) 60FPS (16:9)
WIFI	Connect external USB flash disk (support FAT32 and NTFS formats); picture: JPG format; video: MP4 format
Optical data	Built-in WIFI function, it can transmit images
Video resolution	Camera split ratio: 2.8; beam split ratio: 2.8 (5.5 for option)
Picture resolution	4K 30FPS, 1080P 30FPS
Basic functions	8M (3840*2160), 2M (1920*1080)
Image effect	Freeze, photograph, video recording, automatic exposure, white balance, play back and cross curve, sound recording
Advanced functions	Exposure value, best brightness, gain, red gain, blue gain, saturation, contrast ratio, definition and HDR
System settings	Horizontal flip, vertical flip, zoom out, zoom in, AOI and image comparison
	Automatic/automatic naming, show/hide time, show/hide LOGO, eleven languages for option (Chinese, English, German, French, Spanish, Italian, Portuguese, Swedish, Japanese, Russian, Polish), image resolution, naming setting, system update, restore default, version information

Optional Accessories



Optional Outfits



Optional Outfits



Figure of Support System of AM-5000

